

10549 566

Rec'd PCT/PTO 22 JUN 2006

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 March 2005 (03.03.2005)

PCT

(10) International Publication Number
WO 2005/018895 A1



- (51) International Patent Classification⁷: **B28C 5/38**
- (21) International Application Number:
PCT/US2003/025438
- (22) International Filing Date: 15 August 2003 (15.08.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicants (*for all designated States except US*): **MC NEILUS TRUCK AND MANUFACTURING, INC.** [US/US]; P.O. Box 70, Highway 14 East, Dodge Center, MN 55927 (US). **FAVCO COMPOSITE TECHNOLOGY (US), INC.** [AU/AU]; 39 Shoalhaven Road, Sylvania Waters, Sydney, NSW 2224 (AU). **FAVCO TRUCK MIXERS INTERNATIONAL PTY LIMITED** [AU/AU]; 39 Shoalhaven Road, Sylvania Waters, Sydney, NSW 2224 (AU). **COMPOSITE TECHNOLOGY R & D PTY LIMITED** [AU/AU]; 39 Shoalhaven Road,

Sylvania Waters, Sydney, NSW 2224 (AU). **KHOURI, Anthony, James** [AU/AU]; 39 Shoalhaven Road, Sylvania Waters, Sydney, NSW 2224 (AU). **RODGERS, William** [AU/AU]; 10-12 Childs Road, Chipping Norton, Sydney, NSW 2224 (AU).

- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): **PIHKOVICH, Vadim** [—/—]; * (**).
- (74) Agent: **ANDERSON, Mathew, P.**; Foley & Lardner, 777 East Wisconsin Avenue, Milwaukee, WI 53202-5306 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: MIXING DRUM DRIVE RING



(57) Abstract: A composite, heavy duty rotary concrete mixing drum (16) for coupling to a vehicle having a drivetrain (18) for rotating the drum (16) comprises a wall and a drive ring. The wall defines a first end of the drum and a second end of the drum. The drive ring (39) is coupled to the first end of the drum and includes a hub (108, 252) and a plurality of extensions (110, 254). The hub is operatively coupled to the drivetrain. The plurality of extensions (110, 254) extend outwardly from the hub (108, 252) into the wall of the drum. At least one of the extensions includes an aperture (121, 126) extending therethrough. Rotation of the hub by the second drivetrain causes rotation of the drum.

BEST AVAILABLE COPY

WO 2005/018895 A1



(84) **Designated States (regional):** ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- with amended claims

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

BEST AVAILABLE COPY